

Panther Batterien

Batteriedatenblatt



CTX4L-BS


ETN: GEL 503 0 14 003
DIN: 50314

Specifications

Model NO .	GT9B-4	
Same Dimensions As YUASA Model	YTX4L-BS	
Nominal Voltage	12V	
Rated Capacity (10 hours rate)	4 AH	
Dimension	Length	114 mm (4.49 inches)
	Width	71mm (2.80 inches)
	Height	86 mm (3.38 inches)
	Total Height	86mm (3.38 inches)
Approx. Wight	Approx. 1.69kg (3.72Lbs)	
Charge Current (A)	0.4A	



Dimensions



Characteristics

Capacity 25°C (77°F)	10hours rate (0.4 A to 10.5V)	4.0 Ah
	5hours rate (0.8 A to 10.2V)	3.4Ah
	1C (4.0 A to 9.6V)	1.8Ah
	3C (12.0 A to 9.6V)	1.4Ah
Cold Cranking Amperes(-18°C SAE Standard)		45 A
Cold Cranking Amperes(-18°C EN Standard)		67.5 A
Internal Resistance (at 1KHz)		Apox.9.8m Ω
Operating Temperature Range	Charge 0°C (32°F) to 40°C (104°F)	
	Discharge -15°C (5°F) to 50°C (122°F)	
	Storage -15°C (5°F) to 40°C (104°F)	
Life Expectancy (Cycle Use)	100% depth of discharge 200 cycles	
	80% depth of discharge 225 cycles	
	50% depth of discharge 500 cycles	
Charge Retention (shelf life) at 20°C (68°F)	1 month	92%
	3 month	90%
	6 month	80%
Standby Use	3~5 years	
Case Material	ABS	

