

Panther Batterien

alles startklar!



Energie in Perfektion!



12 V 200 Ah (C20) Deep Cycle AGM Battery

PHYSICAL CHARACTERISTICS		
	SI Units	US Units
Length	518 mm	20.2 inch
Width	276 mm	11.1 inch
Height	242 mm	9.5 inch
Typical weight	57.4 kg	126.5 lbs



AGM200
Typ A200

Specifications:

- Nominal voltage: 12 V
- Rated capacity: 200 Ah (at C₂₀)
- Separator: AGM
- Electrolyte: Sulphuric acid; analytical grade
- Self discharge: < 2.5% per month at 20°C
- Standards: IEC 61056; IEC 61427; IEC 60896
- Venting valve: One way, self resealing
- Degassing system: Central
- Terminal type: Top / Automotive
- Case / lid material: Polypropylene
- Carrying Handles: Available (2)

BATTERY CHARGE CONDITIONS	
Constant current charge	Current range: 0.1 – 0.2C ₂₀ A
Constant voltage charge	Voltage range: 14.10 – 15.10 V (Recommended: 14.40 V)
Float voltage	13.62 V (2.27 Vpc) at 20 °C
Temperature correction factor	Below 20 °C: + 0.018 V/block/°C; Above 20 °C: - 0.018 V/block/°C
Float application	Recommended: max. 0.1C ₁₀ A / 13.62 V (2.27 Vpc)
Cycle applications	Recommended: max. 0.2C ₁₀ A / 14.40 V (2.40 Vpc) Recharge Ah: at least 105% from previous discharge Ah

